

Continental IC 70 Radial Tyres – faster with longer life

IC 70 – exclusive to Continental

Continental is the only tyre manufacturer to offer a radial tyre in this pattern, which is designed for small vehicles working in airports, warehouses and public highways. The IC 70 delivers high average speeds of up to 31 mph over long distances with a tread compound that ensures high mileage performance. Good cushioning and damping gives a comfortable ride so drivers can operate long shifts safely, while low rolling resistance improves fuel efficiency.

Applications

- Electric Forklift Trucks
- Gas & Diesel Forklift Trucks
- Electrical & Diesel Trolley
- Industrial Tractors
- Heavy Duty Trailers
- Trailers



IC 70 Features

Low rolling resistance

Cushioning and shock resistance

Steel belt substantially strengthens tread area

Excellent traction

Superb cornering performance

High mileage performance

Operational Benefits

Excellent fuel economy

Maximum driver comfort reduces driver fatigue

Longer service life

Safer operation on wet roads

Safe and positive handling

Longer service life

IC 70

				Standard value, pneumatic tyres, in service	
Size	Ply Rating	Rim	Article	Width mm	Outer dia. mm
8"					
5.00 R 8	10	3.00 D -8	07050700000	136	476
125/75 R 8 (15 x 4 1/2 R 8)	12	3.00 D-8	07050650000	126 - 129	392
150/75 R 8 (16 x 6 R 8)	16	4.33 R-8	07050840000	160	439
180/70 R 8 (18 x 7 R 8)	16	4.00 E-9	07050880000	182	465
9"					
6.00 R 9	12	5.00 F-10	07051010000	165	551
10"					
6.50 R 10	14	5.50 F-10	07051060000	182 187	600
225/75 R10 (23 x 9 R 10)	20	6.50 F-10	07051110000	239	606
12"					
7.00 R 12	16	5.00 S-12	07051220000	198	685
15"					
7.00 R 15	14	5.5-15	07052650000	203	761
7.50 R 15	16	6.0-15 6.5-15	07052720000	218 - 224	787
8.25 R 15	18	6.5 -15	07052770000	241	853
250/70 R 15 (250 R 15)	18	7.0-15 7.5-15	07052570000	264 - 269	745



For more information phone the Industrial
Hotline on 0845 6000 803 or fax 01895 425 996

**Continental IC 70 Tyres –
faster with longer life**

Continental
TYRES – ENGINEERED IN GERMANY

