

MASTERSOLID



RESILIENT TIRES



The Mastersolid tire is developed with the very latest industrial technology. Quality and state-of-the-art technology guarantees a top-notch product with economical benefits:

- **increased shock absorption**
- **extra long wear qualities**
- **exceptional low rolling resistance**

- **NATURAL RUBBER**
- **GOOD RESISTANCE TO FATIGUE**
- **HIGH STABILITY
MAXIMUM SAFETY**
- **OPTIMAL GRIP
AND TRACTION**



MASTERSOLID

- **TRELLEBORG ENGINEERED**
- **PREMIUM COMPOUNDS**
- **HIGH RELIABILITY**
- **FOR USE IN INDUSTRIAL APPLICATIONS**
- **AVAILABLE IN POPULAR SIZES**



MASTERSOLID

Size	Rim		Plus	Dimensions		Weight kg	Load capacity (kg)				
				max. width	O.D.		Forklift trucks		Other vehicles		
							25 km/h		6 km/h	10 km/h	25 km/h
							drive kg	steer kg	kg	kg	kg
mm ± 2%	mm ± 2%										
3.00 - 4	2.10 C - 4	sl		80	252	3,7	260	195	260	235	195
4.00 - 8	3.00D - 8	sl	✓	104	404	10,7	950	730	950	860	730
4.00 - 8	3.00D - 8	wing		104	404	10,7	950	730	950	860	730
5.00 - 8	3.00D - 8	sl	✓	115	459	10,9	1415	1090	1415	1285	1090
15 x 4 1/2 - 8	3.00 D - 8	sl	✓	104	377	8,9	1040	800	1040	940	800
16 X 6 - 8	4.33 R - 8	sl	✓	132	407	14,4	1455	1120	1455	1320	1120
18 X 7 - 8	4.33 R - 8	sl	✓	145	454	19,8	2145	1650	2145	1950	1650
6.00 - 9	4.00 E - 9	sl	✓	131	519	24,9	1885	1450	1885	1710	1450
21 X 8 - 9	6.00 E - 9	sl	✓	168	523	31,6	2755	2120	2755	2505	2120
6.50 - 10	5.00 F - 10	sl	✓	148	574	34,6	2340	1800	2340	2185	1800
200 / 50 - 10	6.50 F - 10	sl	**	186	456	22,6	2470	1900	2470	2240	1900
23 x 9 - 10	6.50 F - 10	sl	✓	210	584	48,4	3445	2650	3445	3125	2650
7.00 - 12	5.00 S - 12	sl	✓	162	650	44,4	2920	2240	2920	2640	2240
23 x 10 - 12	8.00 G - 12	sl	✓	228	581	46,9	3770	2900	3770	3420	2900
27 x 10 - 12	8.00 G - 12	sl	✓	228	672	68,4	3900	3000	3900	3540	3000
250 - 15	7.0 - 15	sl	✓	210	720	66,5	4640	3570	4640	4200	3570
250 - 15	7.5 - 15	sl		210	720	67,0	4640	3570	4640	4200	3570
300 - 15	8.0 - 15	sl	✓	250	822	113,0	5850	4500	5850	5310	4500
7.00 - 15	5.5 - 15	sl		186	725	58,0	3545	2725	3545	3215	2725
7.50 - 15	5.5 - 15	sl	✓	187	755	65,0	3900	3000	3900	3540	3000
7.50 - 15	6.5 - 15	sl		187	755	66,0	3900	3000	3900	3540	3000
28 x 9 - 15	7.0 - 15	sl	✓	202	681	53,0	3900	3000	3900	3540	3000
8.25 - 15	5.5 - 15	sl		202	823	85,6	4750	3650	4750	4300	3650
8.25 - 15	6.5 - 15	sl	✓	202	823	85,6	4750	3650	4750	4300	3650
10.00 - 20	7.0 - 20	sl		260	1026	167,0	6000	5000	6000	5455	5000
10.00 - 20	7.5 - 20	sl		260	1026	167,0	6000	5000	6000	5455	5000
10.00 - 20	8.0 - 20	sl		260	1026	170,0	6000	5000	6000	5455	5000
465/55 - 20	16.0 - 20	sl		465	1029	319,0	10800	9000	10800	9810	9000

The above load capacities are based on available E.T.R.T.O. specifications for load and steering wheels on counterbalanced forklift trucks.

** Only available in Plus