

DL-P

INDUSTRIAL PNEUMATICS

A reputation of proven dependability, advanced design and the highest standards of quality are all embodied in the DL-P. This deep-treaded, heavy duty tyre has been designed for applications which may still require a pneumatic.



APPLICATIONS

- Diesel/electric/LPG fork lift trucks
- Side loaders
- Ground Support equipment
- Ro-ro trailers
- Skid steer loaders
- Container handling

Advanced tyre technology and manufacturing expertise combine in the production of the DL-P the latest addition to the Watts range of industrial pneumatics. A deep lug tread, providing superior traction, is supported by thick, reinforced side walls for greater strength, stability and longevity.

deep treaded, heavy duty pneumatic

The DL-P is available in a range of popular sizes and ply ratings providing a cost-effective solution for all industrial applications where pneumatic tyres are required.



Certificate No. Q 09672
BSEN ISO 9001:2000



Watts
Industrial Tyres
Moving on Success

D L P : S P E C I F I C A T I O N S

Size	Ply Rating	Tread Pattern	Rim	Inflation Pressure	Load Capacity Fork Lift Truck Use Up to (Kg)			
					Up to 25 Kph		Up to 35 Kph	
					Load	Steer	Load	Steer
5.00-8	8	J	3.00 - 08	8.25	1235	950	1190	880
5.00-8	10	J	3.00 - 08	10.00	1415	1090	1365	1010
15 x 4.5 -8	12	J	3.00 - 08	10.00	1040	800	1000	740
18 x 7 - 8	14	J	4.33 - R8	9.00	1885	1450	1815	1340
18 x 7 - 8	16	J	4.33 - R8	10.00	2145	1650	2065	1525
6.00 - 9	10	J	4.00 - E9	8.50	1715	1320	1650	1220
21 x 8 - 9	14	J	6.00/7.00 - E9	9.00	2535	1950	2435	1805
21 x 8 - 9	16	J	6.00/7.00 - E9	10.00	2755	2120	2650	1960
6.50 - 10	10	J	5.00/5.50 - F10	7.75	1950	1500	1875	1390
23 x 9 - 10	18	J	6.50 - F10	9.00	3160	2430	3040	2250
7.00 - 12	12	J	5.00 - S12	8.50	2680	2060	2575	1905
7.00 - 12	14	J	5.00 - S12	9.00	2755	2120	2650	1960
27 x 10 - 12	12	J	8.00 - G12	6.00	3250	2500	3125	2315
27 x 10 - 12	14	J	8.00 - G12	7.00	3545	2725	3405	2520
7.00 - 15	12	J	5.0/5.50/6.0/6.5 - 15	8.25	3070	2360	2950	2185
7.00 - 15	14	J	5.0/5.50/6.0/6.5 - 15	9.00	3350	2575	3220	2380
7.50 - 15	14	J	5.0/5.50/6.0/6.5 - 15	9.25	3640	2800	3500	2590
8.15 - 15 (28 x 9 - 15)	14	J	7.0 - 15	10.00	3770	2900	3625	2685
8.15 - 15 (28 x 9 - 15)	16	J	7.0 - 15	10.25	4095	3150	3940	2915
8.25 - 15	14	J	6.50/7.0 - 15	8.00	4225	3250	4065	3005
8.25 - 15	16	J	6.50/7.0 - 15	9.25	4615	3550	4440	3285
250 - 15	16	J	7.0/7.5 - 15	8.25	4355	3350	4190	3100
300 - 15	18	J	8.0 - 15	7.50	5850	4500	5625	4165
9.00 - 20	14	B	6.5/7.0/7.5 -15	9.00	5375	4450	5375	4125
10.00 - 20	16	B	6.5/7.0/7.5/8.0 -15	9.00	6000	5000	6250	4625
12.00 - 20	18	B	8.0/8.5/10.0 - 20	9.00	7500	6250	7500	5800
					8Kmh	16Kmh		
10 - 16.5*	8	SSL	8.25 - 16.5	3.75	1750	1360		
12 - 16.5*	10	SSL	9.75/8.25 - 16.5	4.20	2430	1900		

*Tubeless

Tread Patterns



B

J

SSL

All specifications are in accordance with ETRTO (European Tyre and Rim Technical Organisation).
For further information please consult the Watts Technical Department

Distributed by:



Watts Industrial Tyres

Church Road, Lydney, Glos GL15 5EN, U.K.
Tel: +44 (0) 1594 847100 Fax: +44 (0) 1594 842429

E-mail industrial@watts-tyres.co.uk

www.industrialtyre.com