

DL-QZ1

INDUSTRIAL PNEUMATIC

The DL-QZ1 has been specifically developed as a competitively priced option. A reputation for proven dependability, advanced design and the highest standards of quality are all embodied in this latest edition to the Watts range.



APPLICATIONS

- Diesel/electric/LPG fork lift trucks
- Side loaders
- Ground support equipment
- Ro-ro trailers
- Skid steer loaders
- Container handling

Watts DL-QZ1 is available in all popular sizes & ply ratings. Where pneumatic tyres are your preferred choice, the

Value & Performance; A Winning Combination

Watts DL-QZ1 provides value and performance; a winning combination.



CERTIFICATE NO. Q/09672

BSEN ISO 9002



Watts
Industrial Tyres

Moving on Success

DL-QZ1 : SPECIFICATIONS

Size	Ply Rating	Weight	Tread Pattern	Rim	Inflated Dimensions		Inflation Pressure +/- 15%	Load Capacity Fork Lift Truck Use (Kgs)			
					Section Height	Section Width		Up to 25Kph		Up to 35 Kph	
								Load	Steer	Load	Steer
4.00 - 8	8	4.3	QZ1	2.50/3.25-8	415	112	9.00	870	670	840	620
4.00 - 8	10	4.3	QZ1	2.50/3.25-8	415	112	10.00	950	730	915	675
5.00 - 8	8	5.7	QZ1	3.00/3.50-8	470	137	8.25	1235	950	1190	880
5.00 - 8	10	5.5	QZ1	3.00/3.50-8	470	137	10.00	1415	1090	1365	1010
18 x 7 - 8	14	8.6	QZ1	4.33-8	465	173	9.00	1885	1450	1815	1340
18 x 7 - 8	16	8.8	QZ1	4.33-8	465	173	10.00	2145	1650	2065	1525
6.00 - 9	10	9	QZ1	4.00-9	540	160	8.50	1715	1320	1650	1220
6.00 - 9	12	9.2	QZ1	4.00-9	540	160	10.00	1885	1450	1815	1340
7.00 - 9	10	12.9	QZ1	4.33-9	590	190	8.50	2140	1645	2055	1520
7.00 - 9	12	13.2	QZ1	4.33-9	590	190	9.70	3265	1820	2275	1685
6.50 - 10	10	11.3	QZ1	5.00/5.50-10	590	175	7.75	1950	1500	1875	1390
6.50 - 10	12	11.6	QZ1	5.00/5.50-10	590	175	9.00	2145	1650	2065	1525
7.50 - 10	12	15.5	QZ1	5.00/5.50-10	645	205	8.00	2680	2060	2575	1905
23 x 9 - 10	12	14.7	QZ1	6.50-10	595	225	5.75	2405	1850	2315	1710
23 x 9 - 10	18	15	QZ1	6.50-10	595	225	9.00	3160	2430	3040	2250
7.00 - 12	12	15.7	QZ1	5.00/6.50-12	676	190	8.50	2680	2060	2575	1905
7.00 - 12	14	16	QZ1	5.00/6.50 -12	676	190	9.00	2755	2120	2650	1960
8.25 - 12	12	20.7	QZ1	5.00-12	728	210	7.50	3245	2495	3120	2310
27 x 10 - 12	12	19.3	QZ1	8.00-12	690	255	6.00	3250	2500	3125	2315
27 x 10 - 12	14	19.6	QZ1	8.00-12	690	255	7.00	3640	2725	3405	2520
27 x 10 - 12	16	20.1	QZ1	8.00-12	690	255	8.00	3900	3000	3750	2775
7.00 - 15	10	19.1	QZ1	5.00/6.50-15	750	200	7.00	2745	2110	2640	1950
7.00 - 15	12	19.4	QZ1	5.00/6.50-15	750	200	8.25	3070	2360	2950	2185
7.00 - 15	14	19.8	QZ1	5.00/6.50-15	750	200	9.00	3380	2600	3250	2405
7.50 - 15	10	20.2	QZ1	5.00/6.50-15	780	215	6.50	2958	2275	2845	2105
7.50 - 15	12	20.5	QZ1	5.00/6.50-15	780	215	8.00	3445	2650	3315	2450
7.50 - 15	14	21.1	QZ1	5.00/6.50-15	780	215	9.25	3640	2800	3500	2590
8.25 - 15	12	26	QZ1	5.00/7.50-15	840	235	7.00	3900	3000	3750	2775
8.25 - 15	14	26.3	QZ1	5.00/7.50-15	840	235	8.00	4225	3250	4065	3005
8.25 - 15	16	26.4	QZ1	5.00/7.50-15	840	235	9.25	4615	3550	4440	3285
8.25 - 15	18	29.6	QZ1	5.00/7.50-15	840	235	10.00	4745	3650	4565	3375
8.15-15 (28 x 9 - 15)	12	19.3	QZ1	6.50/7.00-15	710	220	7.00	2730	2100	2625	1945
8.15-15 (28 x 9 - 15)	14	19.7	QZ1	6.50/7.00-15	710	220	8.00	2958	2275	2845	2105
8.15-15 (28 x 9 - 15)	16	20.1	QZ1	6.50/7.00-15	710	220	9.00	3170	2440	3050	2255
250 - 15	16	23.8	QZ1	7.00/7.50-15	735	250	8.25	4355	3350	4190	3100

Tread Patterns



QZ1

All specifications are in accordance with ETRTO (European Tyre and Rim Technical Organisation). For further information please consult the Watts Technical Department

Distributed by:



Watts Industrial Tyres

Church Road, Lydney, Glos GL15 5EN, U.K.
Tel: +44 (0) 1594 847100 Fax: +44 (0) 1594 842429

E-mail industrial@watts-tyres.co.uk

www.industrialtyre.com