

HPT-QZ4

INDUSTRIAL PNEUMATICS

Watts HPT-QZ4 heavy duty carcass has a full bead cross-ply construction, with a tough reinforced undertread and bead area, all manufactured to the highest specification, utilising the very latest rubber technology.



Watts HPT-QZ4 with its reinforced sidewall technology and wide profile tread represents a completely new breed of pneumatic tyre design and specification; providing both end users and O.E.Ms alike with a

APPLICATIONS

- Diesel/electric/LPG fork lift trucks
- Side loaders
- Ground support equipment
- Ro-ro trailers
- Skid Steer loaders
- Container Handling

a pneumatic with strength

considerably improved choice in the range of options presently available to them in today's industrial pneumatic tyre market.



Certificate No. Q 09672
BSEN ISO 9001:2000



Watts
Industrial Tyres
Moving on Success

HPT-QZ4- : SPECIFICATIONS

Size	Ply Rating	Tread Pattern	Weight (Kg)	Rim Width		Inflated Dimensions		Inflation Pressure ±15% BAR	Load Capacity Fork Lift Truck Use (Kgs)				Static Loads Kg
				Recommended	Alternative	Section Width	Outside Diameter		Upto 25 Km/h		Upto 35 Km/h		
								Drive	Steer	Drive	Steer		
5.00-8	8	J	7	3.00D	3.25F	155	485	8.25	1235	950	1190	880	1435
5.00-8	10	J	8	3.00D	3.25F	155	485	10	1415	1090	1365	1010	1645
16x6-8	18	J	9	4.33R	-	155	415	10	2225	1710	2140	1580	2580
18x7-8	14	J	10	4.33R	5.00F	180	460	9	1885	1450	1815	1340	2190
18x7-8	16	J	11	4.33R	5.00F	180	460	10	2145	1650	2065	1525	2490
6.00-9	10	J	11	4.00E	-	176	536	8.5	1715	1320	1650	1220	1995
21x8-9	18	J	18	6.00E	7.00E	220	535	10	3020	2320	2900	2145	3500
6.50-10	10	J	14	5.00F	5.50F	190	585	7.25	1950	1500	1875	1390	2265
6.50-10	12	J	15	5.00F	5.50F	190	585	9	2110	1705	1985	1490	2575
23x9-10	18	J	21	6.50F	7	240	575	9	3160	2430	3040	2250	3670
7.00-12	12	J	19	5.00S	-	205	675	8.5	2680	2060	2575	1905	3110
7.00-12	14	J	20	5.00S	-	205	675	9	2755	2120	2650	1960	3200
23x10-12	22	J	28	8.00G	-	260	595	10.25	4545	3495	4370	3235	5280
27x10-12	20	J	30	8.00G	-	270	690	10	4615	3550	4440	3285	5360
7.00-15	12	J	20	5.5	5	200	740	8.25	3070	2360	2950	2185	3565
7.00-15	14	J	21	5.5	5	200	740	9	3350	2575	3220	2380	3890
7.50-15	14	J	25	6	6.5	215	785	9	3640	2800	3500	2590	4230
8.15-15	12	J	23	7	-	235	720	8.5	3445	2650	3315	1650	4000
8.15-15	14	J	24	7	-	235	720	10	3770	2900	3625	2685	4380
8.15-15	16	J	26	7	-	235	720	10.25	4095	3150	3940	2915	4755
8.25-15	12	J	34	6.5	7	255	835	7	3900	3000	3750	2775	4530
8.25-15	14	J	35	6.5	7	255	835	8	4225	3250	4065	3005	4910
8.25-15	16	J	36	6.5	7	255	835	9.25	4615	3550	4440	3285	5360
250-15	16	J	37	7.5	7	245	735	8.25	4355	3350	4190	3100	5060
250-15	18	J	38	7.5	7	245	735	9.5	4745	3650	4565	3380	5510
300-15	18	J	45	8	-	280	810	7.5	5850	4500	5625	4165	6795
300-15	20	J	46	8	-	280	810	9.5	6340	4875	6095	4510	7360
28x12.5-15	24	J	42	9.75	-	305	705	10	6015	4625	5780	4280	5700
32x12.1-15	24	J	58	9.75	-	320	805	10	7800	6000	7500	5550	7440
10.00-20	16	J	80	7.5	8	300	1065	9	6000	5000	5750	4625	7550
10.00-20	20	J	86	7.5	8	300	1065	10.25	6660	5120	6400	4740	7730
12.00-20	18	J	100	8.5	8	335	1130	9	7500	6250	7500	5800	9440
12.00-20	20	J	105	8.5	8	335	1130	10.25	8250	6850	8250	6400	10345
										8 kmh	16 kmh		
*23x8.50-12	8	SSL	12	7	7.00JA	210	576	4	1050	850			
*27x8.50-15	8	SSL	15	7.00JA	-	205	680	4	1230	1020			
*10-16.5	10	SSL	22	8.25	-	302	763	4.5	2020	1860			
*12-16.5	12	SSL	37	9.75	8.25	325	820	4.75	2660	2200			

*Tubeless
Tread Patterns



J



SSL

All specifications are in accordance with ETRTO (European Tyre and Rim Technical Organisation).
For further information please consult the Watts Technical Department

Distributed by:



Watts

Industrial Tyres

Church Road, Lydney, Glos GL15 5EN, U.K.
Tel: +44 (0) 1594 847100 Fax: +44 (0) 1594 842429

E-mail industrial@watts-tyres.co.uk

www.industrialtyre.com